



FABRICANT DE MATERIEL AGRICOLE

Abbaye de Bonport  
27340 PONT DE L'ARCHE  
☎02.35.23.27.62  
☎02.35.23.27.78  
✉contact@delimbe.com  
[www.delimbe.fr](http://www.delimbe.fr)

## DPA ISO BOX SETTINGS AND INSTRUCTIONS

**DPA on 7-pin tractor plug DPA speed control and lift cut-off at end of field for T24 and T28 DPA**

**Before commissioning your control box on a 7-pin tractor plug, please calculate the flow rate by referring to the settings table for your machine.**

1. Thanks to the graduated potentiometer, set the flow rate of your machine, as indicated on the setting table.

2. Plug in your 7-pin plug in the tractor cab and switch on your machine, sowing and ventilation ON and start seeding.

3. After adjusting your flow rate on the graduation, start sowing until you reach your desired working speed, press the memorised speed switch (just one press). You are now programmed in DPA. The red light will stop flashing and the green light come on. At the end of the field, the seeder stops automatically.

4. The “amorçage” switch is used to turn the seeding rotor without moving it forward (this is useful for seeding field corners).

The red light comes on if your DPA is deprogrammed or if you are stopped with the tractor.




ISO PLUG  
7 PIN

X4G (ISO 11786)

3. Régime de la PDF arrière

2. Vitesse d'avancement théorique

1. Vitesse d'avancement réelle (Radar)



7. Masse

4. Position travail (0V) /  
Position repos (12V)

5. Position du relevage  
arrière (0-10V)

6. Alimentation 12V  
Max 5A

# DPA ISO BOX SETTINGS AND INSTRUCTIONS + WIDTH ADJUSTMENT

**DPA on 7-pin tractor plug DPA speed control and lift cut-off at end of field for T24 and T28 DPA**

**Before commissioning your control box on a 7-pin tractor plug, please calculate the flow rate by referring to the settings table for your machine.**

1. Thanks to the graduated potentiometer, set the flow rate of your machine, as indicated on the setting table.

2. Plug in your 7-pin plug in the tractor cab and switch on your machine, sowing and ventilation ON and start seeding.

3. After adjusting your flow rate on the graduation, start sowing until you reach your desired working speed, press the memorised speed switch (just one press). You are now programmed in DPA. The red light will stop flashing and the green light come on. At the end of the field, the seeder stops automatically.

4. The graduated potentiometer on the plate is used to set your working width. Note that the numbers 0 to 30 do not correspond to the number of metres. You need to do some tests before starting work (ballistics depending on the product).

5. The “amorçage” switch is used to turn the seeding rotor without moving it forward (this is useful for seeding field corners).



The red light comes on if your DPA is deprogrammed or if you are stopped with the tractor.




**ISO PLUG  
7 PIN**



**X4G (ISO 11786)**

- 3. Régime de la PDF arrière
- 2. Vitesse d'avancement théorique
- 1. Vitesse d'avancement réelle (Radar)



7. Masse

- 4. Position travail (0V) / Position repos (12V)

- 5. Position du relevage arrière (0-10V)

- 6. Alimentation 12V Max 5A

## RECOMMENDATIONS FOR USE :

You can calculate the flow rate based on your data (working width x speed x dose/hectare). To calculate the flow rate simply, we have an Excel table which calculates the flow rate automatically and gives you the result depending on your speed. On the Excel table, you need to click on the sheet corresponding to the model of your seed drill and follow the steps for using it. The first table at the top left is used to enter your data (width/speed/dose) and give you the result of the flow rate obtained in kg/hour. The second table below indicates the setting number to be used on the control box and gives you the numbers for each rotor. The choice of rotor is made using the “seeder document” (*the seeder is a document that suggests the type of rotor to use depending on the seed and seeder*). Finally, using the results obtained, choose the setting closest to your flow rate.

Once you have the position of your setting, simply turn the switch manually to the number. Then connect your 7-pin plug to the tractor's speed information plug and switch on the seeder, activate seeding and ventilation (press ON) and start seeding (as indicated in step 2).

Sow until you reach your desired working speed, then press the memorised speed switch (just one press). The red light will stop and the green light will come on, flashing and then fixed, indicating that the DPA is operating and programmed. At this point, if you speed up or slow down, the flow rate will adapt; it is proportional to the forward speed.

## ADDITIONAL INFORMATION:

- **Memorised speed:** The speed will always remain memorised on the DPA box even if you disconnect it from the tractor. The speed will always remain memorised unless the "memorised speed" switch is pressed again.
- **“Amorçage”:** The amorçage switch allows you to turn the seeding rotor without moving forward, which is useful for seeding in the corners of the field or for weighing. As soon as you release the switch, the DPA starts to operate normally.
- **Switches:** The seeding and ventilation switches are toggle switches (ON/OFF) and the memorised speed and “amorçage” switches are pushbutton switches. The dimmer switch is a potentiometer allowing you to adjust your flow rate.
- **Red light:** The red light comes on when the tractor is stopped or when the DPA is not programmed. This does not mean that your motor is faulty, it indicates that the motor is at a standstill because the tractor has stopped.
- **Lift cut-off:** With the ISO DPA, the automatic cut-off at the end of the field applies to mounted tools, but this does not apply to semi-mounted tools. The cut-off is automatic as soon as you lift is lifted. For semi-mounted tools, we propose a lift cut-off option to be added with the DPA.

## **EXAMPLE :**

*Example using a standard T18 seed drill with 40-turn motors*

You want to sow slug pellets at 15 km/h, with a working width of 28 meters and a dose per hectare of 4 kg. Your flow rate is 168 kg/h. The table shows that the yellow or red rotor should be used for a flow rate of 168 kg/h. Choose the closest setting number, i.e. number 7 for yellow rotor or number 3 for red rotor. Turn the graduated wheel on the control box to number 7 for yellow rotor or number 3 for red rotor.

*For the best use of this equipment, please follow these recommendations. The DELIMBE team would like to thank you for your trust.*